




DYNAMIC APPLICATION

PMXX[®] SERVO

DESCRIPTION

High-performance UL/CSA certified flexible servomotor cables designed for Dynamic application in high-speed drag chains, between the motor and frequency converter. The polyurethane outer jacket provides excellent resistance properties against mechanical stress and chemical agents, making these cables suitable for indoor or outdoor use, even in very low temperatures. Screening from electromagnetic interference is achieved thanks to the dense braid Shield.

APPROVALS



2014/35/CEE



2011/65/UE



1907/2006



AWM STYLE 20234 80°C
1000V
File E244280



AWM I/II A/B 80°C
1000V

TECHNICAL DATA



DYNAMIC
-40°C / +80°C
STATIC
-50°C / +80°C



NOMINAL VOLTAGE
1000V (UL/CSA AWM)



TEST VOLTAGE
4000 V

CONSTRUCTION FEATURES

POWER CONDUCTORS	CONDUCTOR	CL6 EXTRA-FLEXIBLE (IEC 60228) BARE COPPER
	INSULATION	POLYOLEFIN
	INSULATION COLOUR	BK. U/L1, V/L2, W/L3, + G/Y
OVERALL STRANDING	SCREEN	SCREEN TINNED COPPER 85% ±5%
	SEPARATION LAYER	TAPE NON-WOVEN TAPE
	SHEATH	POLYURETHANE (TPU)
	SHEATH COLOUR	ORANGE, RAL: 2003, DESINA: YES

TECO CODE	N° CORES X CROSS-SECTION	CUT	ROLLS (M)	DRUMS (M)	EXT Ø (MM)	WEIGHT (KG/KM)
27269	(4G1,5+2X0,5)ST (4GAWG16+2XAWG21)ST	✓		500	11.8	195
15764	(4G35)ST (4GAWG02)ST	✓			29.5	1850
15765	(4G50)ST (4GAWG1/0)ST	✓			35.5	2550
30397	(4G70)ST (4GAWG2/0)ST	✓			40.5	3780
30398	(4G95)ST (4GAWG3/0)ST	✓			46	5130

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.
Company managed and coordinated by Erredue S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.