

STATIC APPLICATION

TC-ER POWER&CONTROL MULTICORE-SH

APPLICATIVE FEATURES



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
1.00	95.00	occ. flexing 15xø	6xø

APPROVALS



TC-ER 90°C 600V



MTW 90°C 600V



AWM STYLE 21179
90°C 1000V



AWM I/II A/B 90°C
1000V



CSA CIC-TC-ER
90°C 600V



2014/35/CEE



2014/30/EU



2011/65/UE



1907/2006

TECHNICAL DATA



STATIC -40°C +90°C
OCCASIONAL FLEXING -5°C
+90°C



NOMINAL VOLTAGE UL AWM =
90°C 1000 V; UL TC-ER / MTW =
600 V; IEC/VDE = 600/1000 V;
CSA = 90°C 1000 V; CSA CIC/TC -
ER = 90°C 600 V



TEST VOLTAGE 2000V (ACC. TO
UL 1277 TAB. 14.1); 4000V (ACC.
TO UL 758 TAB. 29.1)



INSULATION RESISTANCE ≥ 200
MΩ X KM

CONSTRUCTION FEATURES

POWER CONDUCTORS	CONDUCTOR	CL5 FLEXIBLE. BARE COPPER.
	INSULATION	PVC COMPOUND.
	INSULATION COLOR	BLACK CORE WITH WHITE PRINTED NUMBER + GREEN YELLOW
OVERALL STRANDING	FILLER	FILLER NOT HYGROSCOPIC, PRODUCED OUT OF SUITABLE MATERIALS
	SEPARATION LAYER	TAPE POLYESTER TRANSPARENT.
	SCREEN	SCREEN TINNED COPPER 85 % ± 5 %
	SHEATH	PVC COMPOUND.
	SHEATH COLOUR	GRAY , RAL: 7001, DESINA: NO

PRODUCTS FEATURES

FIRE PERFORMANCE

UL 1581 SECTION 1160 (UL VERTICAL-TRAY FLAME TEST)
CSA FT4, FT1, FT2
UL 1581 VW-1 / CABLE FLAME TEST
UL 1685 – FT4/IEEE 1202 VERTICAL FLAME TEST
IEC 60332-1-2



OIL PERFORMANCE

OIL RES I, UL 1277, UL 1063 , VDE 0473-811-404, IEC 60811-404, UL 1581



UV PERFORMANCE

SUN RESISTANT UL 1277 TAB.20



WATER PERFORMANCE

UL 90° DRY
UL WET APPROVAL 75°C



MUD PERFORMANCE

UL 1277 - DIR BUR (DIRECT BURIAL) ACC. TO NFPA 70
UL TYPE TC (TRAY CABLE) - ER (EXPOSED RUN) ACC. TO UL 1277

TECO CODE	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
36437	(2X1,00)ST (2XAWG18)ST	✓	100	500	8.6	95
27551	(3G1,00)ST (3GAWG18)ST	✓	100	500	9	120
27552	(3G1,50)ST (3GAWG16)ST	✓		500	9.2	130
34337	(3G2,50)ST (3GAWG14)ST	✓		500	10.6	188
27553	(4G1,00)ST (4GAWG18)ST	✓		500	9.9	140
27554	(4G1,50)ST (4GAWG16)ST	✓		500	10.8	180
27555	(4G2,50)ST (4GAWG14)ST	✓		500/1000	11.7	240
27556	(4G4,00)ST (4GAWG12)ST	✓			13.3	330
27557	(4G6,00)ST (4GAWG10)ST	✓			15.3	475
27558	(4G10,00)ST (4GAWG08)ST	✓			19.8	766
27559	(4G16,00)ST (4GAWG06)ST	✓			25	1201
27560	(4G25,00)ST (4GAWG04)ST	✓			28.7	1694
36865	(4G35,00)ST (4GAWG02)ST	✓			31.5	2203
39292	(4G50,00)ST (4GAWG01)ST	✓			39	3100
43307	(4G70,00)ST (4GAWG2/0)ST	✓			44	4160
43308	(4G95,00)ST (4GAWG3/0)ST	✓			48.6	3960
27561	(5G1,00)ST (5GAWG18)ST	✓		500	10.6	170
30480	(5G1,50)ST (5GAWG16)ST	✓		500	11.7	240
28986	(7G1,00)ST (7GAWG18)ST	✓		500	11.7	211
27562	(7G1,50)ST (7GAWG16)ST	✓		500	12.7	270
27563	(7G2,50)ST (7GAWG14)ST	✓			14.5	390
39270	(7G4,00)ST (7GAWG12)ST	✓			16.2	545
34937	(12G1,00)ST (12GAWG18)ST	✓			15.7	350
27564	(12G1,50)ST (12GAWG16)ST	✓			17.2	445
27565	(12G2,50)ST (12GAWG14)ST	✓			18.6	606
39271	(12G4,00)ST (12GAWG12)ST	✓			21.4	815
39272	(18G1,00)ST (18GAWG18)ST	✓			18.2	485
39273	(18G1,50)ST (18GAWG16)ST	✓			20	625
39274	(18G2,50)ST (18GAWG14)ST	✓			23	848
39275	(18G4,00)ST (18GAWG12)ST	✓			26	1210
36438	(25G1,00)ST (25GAWG18)ST	✓			21	605

TECO CODE	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
36439	(25G1,50)ST (25GAWG16)ST	✓			23.7	767

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.
Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.

