

# STATIC APPLICATION

## TECNIFLEX® POWER&CONTROL MULTICORE BK 0,6-1KV

### APPLICATIVE FEATURES



#### MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0.50	95.00	occ. flexing 15xØ	6xØ

### APPROVALS



CPR 305/11 Eca CPR ECA



### TECHNICAL DATA



INSTALLATION 0°C +70°C  
STATIC -40°C +80°C  
OCCASIONAL FLEXING -5°C  
+70°C



NOMINAL VOLTAGE 0,6/1KV



TEST VOLTAGE 4000V (C/C)



INSULATION RESISTANCE > 20  
GOHM X CM

### CONSTRUCTION FEATURES

POWER CONDUCTORS	CONDUCTOR	CL5 FLEXIBLE. BARE COPPER.
	INSULATION	PVC COMPOUND.
	INSULATION COLOR	BLACK CORE WITH WHITE PRINTED NUMBER + GREEN YELLOW
OVERALL STRANDING	FILLER	FILLER SUITABLE
	TALC	TALC POWDER
	SHEATH	PVC COMPOUND.
	SHEATH COLOUR	MATTE BLACK , RAL: 9005, DESINA: NO

### PRODUCTS FEATURES



#### FIRE PERFORMANCE

IEC EN 60332-1-2; DIN VDE 0482-  
332-1-2



#### OIL PERFORMANCE

EN 50290-2-22 TM54 (CEI 20-  
34/0-1; 4 H / 70°C, OLIO IRM 902)  
VDE 0819 PART 102



#### UV PERFORMANCE

EN ISO 4892-3-2006 OR EN ISO  
4892-2-2013, METHOD A (COLOUR  
CHANGING ALLOWED)  
ACC. TO EN 50525-1 RISP. VDE  
0285-525-1 BLACK SHEATH  
CABLES ARE SUITABLE FOR  
OUTDOOR PERMANENT USAGE.  
NF C 32-321 AND RELATIVE  
ANNEXE A  
UV TEST REFERENCE:  
ISO 4892-2-2013  
ISO 4892-3-2006  
DIN EN ISO 4892-2

TECO CODE	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]	INS. COLOUR EXC
34295	2X1,00	✓	100	500	7.2	75	
34302	2X1,50	✓	100	500	8.5	110	
34310	2X2,50	✓		500	9.5	150	
39280	3G0,75	✓	100	500	7	74	
34296	3X1,00	✓	100	500	7.6	90	BLACK CORE WITH WHITE PRINTED NUMBERS.
34297	3G1,00	✓	100	500	7.6	90	
34303	3G1,50	✓	100	500	9	130	
36848	3X1,50	✓	100	500	9	130	BLACK CORE WITH WHITE PRINTED NUMBERS.
34938	3G2,50	✓		500	10.3	185	
34298	4X1,00	✓	100	500	8.4	115	BLACK CORE WITH WHITE PRINTED NUMBERS.
34299	4G1,00	✓	100	500	8.4	115	
34304	4G1,50	✓	100		9.6	155	
34311	4G2,50	✓		500	11.3	225	
34314	4G4,00	✓		500	13	315	
34316	4G6,00	✓			14.6	420	
34317	4G10,00	✓			18.5	680	
35507	4G16,00	✓			21.8	980	
35508	4G25,00	✓			27.4	1479	
35509	4G35,00	✓			30.1	1961	
34300	5G1,00	✓		500	9.2	140	
34305	5G1,50	✓		500	10.5	230	
34312	5G2,50	✓		500	12.5	280	
34301	7G1,00	✓		500	10	170	
34306	7G1,50	✓		500	11.5	230	
34313	7G2,50	✓			13.8	355	
34334	12G1,00	✓		500	13	260	
34307	12G1,50	✓			15.5	385	
34335	18G1,00	✓			15.7	395	
34308	18G1,50	✓			18.2	550	
34336	25G1,00	✓			18.6	540	
34309	25G1,50	✓			21.9	760	

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.  
Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.