


DYNAMIC APPLICATION

PMXX® PLUS SERVO



APPLICATIVE FEATURES



**UP TO 5 MILLION
GUARANTEED CYCLES**



**50,0 M/S²
ACCELERATION**



**25,0 M
CABLE LENGTH**



**300,0 M/MIN
TRAVEL SPEED**



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0.50	16.00	6xØ	3xØ
25.00	95.00	10xØ	5xØ

APPROVALS



**AWM STYLE 21209
90°C 1000V**



**AWM I/II A/B 90°C
1000V**



2014/35/CEE



2014/30/EU



2011/65/UE



1907/2006



**IEC 60754-1
EN 50267-1**

TECHNICAL DATA



STORAGE
-50°C +80°C
DYNAMIC
-30°C +90°C
STATIC
-40°C +90°C



NOMINAL VOLTAGE
1000 V (UL/CSA) U₀/U 0,6/1 KV
(VDE)



TEST VOLTAGE
4,0 KV
TEST VOLTAGE REFERENCE
EN 50395 PART 6-7
UL/1581



INSULATION RESISTANCE
≥1 GOHM/KM(20°C)
≥10 MOHM/KM(90°C)

CONSTRUCTION FEATURES

POWER CONDUCTORS	CONDUCTOR	CL6 EXTRA-FLEXIBLE. BARE COPPER.
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	BLACK CORE WITH WHITE PRINTING (U/L1/C/L+ V/L2 W/L3/D/L-) + GREEN-YELLOW.
	SEPARATION LAYER	INNER TAPE POLYESTER TRANSPARENT TAPE OR NON-WOVEN TAPE
OVERALL STRANDING SERVO	FILLER	FILLER POLYPROPYLENE
	SEPARATION LAYER	TAPE NON-WOVEN TAPE
	SCREEN	SCREEN TINNED COPPER 85 % ± 5 %
	SEPARATION LAYER	TAPE NON-WOVEN TAPE
	SHEATH	POLYURETHANE COMPOUND (TMPU)
	SHEATH COLOUR	ORANGE, RAL: 2003, DESINA: YES

PRODUCTS FEATURES



FIRE PERFORMANCE
SELF-EXTINGUISHING AND FLAME
RETARDANT ACC. TO DIN VDE 0482-
332-1-2

DIN EN 60332-1-2
IEC 60332-1-2
UL 1581 SEC.1061 CABLE FLAME
UL VW-1
CSA FT1



OIL PERFORMANCE
VDE 0207-363-10-2
IEC 60811-404 (EU)
CEI EN 50363-10-2
1581 (UL)



UV PERFORMANCE
ACCORDING TO ISO 4892-2
EN 50289-4-17
ASTM-D-2565-16
EN 50618



WATER PERFORMANCE
UL 1581
IEC 60811-1-3
EN 50396 (HYDROLYSES
RESISTANCE)



COLD PERFORMANCE
EN 60811-1-4



ABRASION PERFORMANCE
ASTM D 4060



MUD PERFORMANCE
NEK TS 606
IEC 60092-360 ANNEX C+D



MICROBE PERFORMANCE
VDE 0282/10



HOZONE PERFORMANCE
EN 50396 MET. B

TECO CODE	OEM REF.	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
46158		(3G1,50)ST (3GAWG16)ST	✓	100	500	8.2	110
46159		(3G2,50)ST (3GAWG14)ST	✓		500	9.6	170
46160		(4G1,00)ST (4GAWG18)ST	✓	100	500	8.2	100
46161	SIEMENS 6FX8008-1BB11	(4G1,50)ST (4GAWG16)ST	✓	100	500	9	140
46162	SIEMENS 6FX8008-1BB21	(4G2,50)ST (4GAWG14)ST	✓		500	10.6	198
46163	SIEMENS 6FX8008-1BB31	(4G4,00)ST (4GAWG12)ST	✓		500/100	12.3	265
46164	SIEMENS 6FX8008-1BB41	(4G6,00)ST (4GAWG10)ST	✓		100	14.5	400
46165	SIEMENS 6FX8008-1BB51	(4G10,00)ST (4GAWG08)ST	✓			17.5	590
46166	SIEMENS 6FX8008-1BB61	(4G16,00)ST (4GAWG06)ST	✓			21.6	1010
46167	SIEMENS 6FX8008-1BB25	(4G25,00)ST (4GAWG04)ST	✓			25	1480
46168	SIEMENS 6FX8008-1BB35	(4G35,00)ST (4GAWG02)ST	✓			29.4	1950
46169	SIEMENS 6FX8008-1BB50	(4G50,00)ST (4GAWG01)ST	✓			34	2850
46170	SIEMENS 6FX5008-1BB70	(4G70,00)ST (4GAWG2/0)ST	✓			39.9	3965
46171	SIEMENS 6FX8008-1BB95	(4G95,00)ST (4GAWG3/0)ST	✓			47.5	5200

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.
Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.