

# DYNAMIC APPLICATION

## PMXX® PLUS SERVO

### APPLICATIVE FEATURES



UP TO 5 MILLION  
GUARANTEED CYCLES



50,0 M/S<sup>2</sup>  
ACCELERATION



25,0 M  
CABLE LENGTH



300,0 M/MIN  
TRAVEL SPEED



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0.50	16.00	6xØ	3xØ
25.00	95.00	10xØ	5xØ

### APPROVALS



AWM STYLE 21209  
90°C 1000V



AWM I/II A/B 90°C  
1000V



2014/35/CEE



2014/30/EU



2011/65/UE  
2015/863/UE



IEC 60754-1  
EN 50267-1

### TECHNICAL DATA



STORAGE -50°C +80°C  
DYNAMIC -30°C +90°C  
STATIC -40°C +90°C



NOMINAL VOLTAGE 1000 V  
(UL/CSA) UO/U 0,6/1 KV (VDE)



TEST VOLTAGE 4,0 KV  
TEST VOLTAGE REFERENCE EN  
50395 PART 6-7, UL/1581



INSULATION RESISTANCE ≥1  
GOHM/KM

### CONSTRUCTION FEATURES

POWER CONDUCTORS	CONDUCTOR	CL6 EXTRA-FLEXIBLE. BARE COPPER.
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	BLACK CORE WITH WHITE PRINTING ( U/L1/C/L+, V/L2, W/L3/D/L-) + GREEN-YELLOW.
	SEPARATIONLAYER	INNER TAPE POLYESTER TRANSPARENT TAPE OR NON-WOVEN TAPE
OVERALL STRANDING SERVO	FILLER	FILLER POLYPROPYLENE
	SEPARATIONLAYER	TAPE NON-WOVEN TAPE
	SCREEN	SCREEN TINNED COPPER 85 % ± 5 %
	SEPARATIONLAYER	TAPE NON-WOVEN TAPE
	SHEATH	POLYURETHANE COMPOUND (TMPU)
	SHEATH COLOUR	ORANGE , RAL: 2003, DESINA: YES

## PRODUCTS FEATURES

### FIRE PERFORMANCE

Self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2, UL Cable flame, UL VW-1, CSA FT1.



### OIL PERFORMANCE

VDE 0473-811-404, IEC 60811-404 (EU), CEI EN 50363-10-2, 1581 (UL)



### UV PERFORMANCE

according to ISO 4892-2, EN 50289-4-17, ASTM-D-2565-16



### WATER PERFORMANCE

UL 1581 - IEC 60811-1-3



### COLD PERFORMANCE

EN60811-1-4



### ABRASION PERFORMANCE

ASTM D 4060



### MUD PERFORMANCE

Nek 606



### MICROBE PERFORMANCE

VDE 0282/10



### HOZONE PERFORMANCE

EN 50396 art. 8.1.3

TECO CODE	OEM REF.	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
46158		<b>(3G1,50)ST</b> (3GAWG16)ST	✓	100	500	8.2	110
46159		<b>(3G2,50)ST</b> (3GAWG14)ST	✓		500	9.6	170
46160		<b>(4G1,00)ST</b> (4GAWG18)ST	✓	100	500	8.2	100
46161	SIEMENS 6FX8008-1BB11	<b>(4G1,50)ST</b> (4GAWG16)ST	✓	100	500	9	140
46162	SIEMENS 6FX8008-1BB21	<b>(4G2,50)ST</b> (4GAWG14)ST	✓		500	10.6	198
46163	SIEMENS 6FX8008-1BB31	<b>(4G4,00)ST</b> (4GAWG12)ST	✓		500/100	12.3	265
46164	SIEMENS 6FX8008-1BB41	<b>(4G6,00)ST</b> (4GAWG10)ST	✓		100	14.5	400
46165	SIEMENS 6FX8008-1BB51	<b>(4G10,00)ST</b> (4GAWG08)ST	✓			17.5	590
46166	SIEMENS 6FX8008-1BB61	<b>(4G16,00)ST</b> (4GAWG06)ST	✓			21.6	1010
46167	SIEMENS 6FX8008-1BB25	<b>(4G25,00)ST</b> (4GAWG04)ST	✓			25	1480
46168	SIEMENS 6FX8008-1BB35	<b>(4G35,00)ST</b> (4GAWG02)ST	✓			29.4	1950
46169	SIEMENS 6FX8008-1BB50	<b>(4G50,00)ST</b> (4GAWG01)ST	✓			34	2850
46170	SIEMENS 6FX5008-1BB70	<b>(4G70,00)ST</b> (4GAWG2/0)ST	✓			39.9	3965
46171	SIEMENS 6FX8008-1BB95	<b>(4G95,00)ST</b> (4GAWG3/0)ST	✓			47.5	5200

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.

Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.