

DYNAMIC APPLICATION

FRX® PLUS ENCODER&RESOLVER 2

APPLICATIVE FEATURES



UP TO 5 MIO
GUARANTEED CYCLES



10,0M/SEC²
ACCELERATION



20,0M
CABLE LENGTH



180,00M/MIN
TRAVEL SPEED



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0,14	1.00	7.5xØ	6.0xØ

APPROVALS



AWM STYLE 20042
90°C 300V



AWM I/II A/B 90°C
300V



2014/35/CEE



2014/30/EU



2011/65/UE



1907/2006

TECHNICAL DATA



DYNAMIC -5 °C +90 °C
STATIC -40 °C +90 °C



NOMINAL VOLTAGE 300V
(UL/CSA)



TEST VOLTAGE C/C
2000VRMS,1MIN;
CORE/OVERALL SCREEN
2000VRMS,1MIN



INSULATION RESISTANCE ≥1
GOHM/KM






CONSTRUCTION FEATURES

GROUP 1	CONDUCTOR	CL6 EXTRA-FLEXIBLE. TINNED COPPER
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	COLOURS SEQUENCE REFERS TO DIN 47100 STANDARD.
	DRAINWIRE	DRAIN WIRE TINNED COPPER
	SEPARATIONLAYER	WRAPPING TAPE SCREEN ALLUMINIUM INSIDE/POLYESTER OUTSIDE
	SEPARATIONLAYER	TAPE POLYESTER TRANSPARENT.
GROUP 2	CONDUCTOR	CL6 EXTRA-FLEXIBLE. TINNED COPPER
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	COLOURS SEQUENCE REFERS TO DIN 47100 STANDARD.
GROUP 3	CONDUCTOR	CL6 EXTRA-FLEXIBLE. TINNED COPPER
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	VARIOUS COLOURS

CONSTRUCTION FEATURES

OVERALL STRANDING	SEPARATION LAYER	WRAPPING NON-WOVEN TAPE
	SCREEN	SCREEN TINNED COPPER 85 % ± 5 %
	SEPARATION LAYER	OVERALL WRAPPING NON-WOVEN TAPE
	SHEATH	PVC COMPOUND.
	SHEATH COLOUR	GREEN , RAL: 6018, DESINA: YES

PRODUCTS FEATURES

	FIRE PERFORMANCE DIN VDE 0482-332-1-2; DIN EN 60332-1-2; IEC 60332-1-2; UL CABLE FLAME; UL VW-1; CSA FT1.		OIL PERFORMANCE VDE 0473-811-404; IEC 60811-404 (EU); CEI EN 50363-4-1 (EU); 1581 (UL)		UV PERFORMANCE CEI EN 50289-4-17, ISO 4892-2, ASTM-D-2565-16
	WATER PERFORMANCE UL 1581, IEC 60811		HYDROCARBONS PERFORMANCE UL 1581		

TECO CODE	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]	INS. COLOUR EXC
46627	[(2X0,34)CCSN+6X2X0,34+2X1,00]ST [(2XAWG22)CCSN+6X2XAWG22+2XAWG18]ST	✓			11	180	GROUP 1 2X0,34 : WH-BN GROUP 2 6X2X0,34 : GN-YE, GY-PK, BU-RD, BK-VT, WH/GN*-BN/GN*, GY/PK*-RD/BU* GROUP 3 2X1,00 : RD-BU *RINGED BICOLOUR

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.
Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.