

STATIC APPLICATION

LIYCY/LIYCY(TP) SIGNAL-ST

APPLICATIVE FEATURES



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0.14	1.50	occ. flexing 10 x Ø	6xØ

APPROVALS



2014/35/CEE



2014/30/EU



2011/65/UE



1907/2006

TECHNICAL DATA



STATIC -40°C +80°C
OCCASIONAL FLEXING -5°C
+80°C



MAX OPERATING VOLTAGE 0,14
MM² = 350 V ; ≥ 0,25 MM² = 500
V (NOT FOR POWER
APPLICATIONS)



TEST VOLTAGE (CORE/CORE)
0,14 - 0,25 MM² = 1200 V 0,34 -
1,50 MM² = 2000 V
(CORE/SCREEN) 0,14 - 0,25 MM²
= 800 V 0,34 - 1,50 MM² = 1200 V



INSULATION RESISTANCE > 20
GOHM X CM

CONSTRUCTION FEATURES

SIGNAL CONDUCTORS	CONDUCTOR	CL5 FLEXIBLE. BARE COPPER.
	INSULATION	PVC COMPOUND.
	INSULATION COLOR	COLOURS SEQUENCE REFERS TO DIN 47100 STANDARD.
OVERALL STRANDING	FILLER	FILLER NOT HYGROSCOPIC, PRODUCED OUT OF SUITABLE MATERIALS
	DRAINWIRE	DRAIN WIRE TINNED COPPER
	SCREEN	SHIELD TINNED COPPER 85 % ± 5 %
	SHEATH	PVC COMPOUND.
	SHEATH COLOUR	GRAY , RAL: 7001, DESINA: NO

PRODUCTS FEATURES



FIRE PERFORMANCE

IEC EN 60332-1-2; DIN VDE 0482-
332-1-2



OIL PERFORMANCE

EN 50290-2-22 TM54 (CEI 20-
34/0-1; 4 H / 70°C, OIL IRM 902);
VDE 0819 PARTE 102.

TECO CODE	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
21803	(1X0,50)ST	✗	100	500	3.5	40
8581	(2X0,14)ST	✗	100	500	3.8	20
5797	(2X0,25)ST	✗	100	500	4.4	29.5
20716	(2X0,34)ST	✗	100	500	4.7	38
5745	(2X0,50)ST	✗	100	500	5.4	45
7048	(2X1,00)ST	✓	100		6.2	65
11979	(3X0,14)ST	✗	100	500	4	27
5746	(3X0,25)ST	✗	100	500	4.6	34.5
11163	(3X0,34)ST	✓	100	500	5.2	44
7348	(3X0,50)ST	✗	100	500	5.7	55
5747	(4X0,25)ST	✗	100	500	5.2	43
11164	(4X0,34)ST	✓	100	500	5.4	51
5748	(4X0,50)ST	✗	100		6.2	61
10341	(4X0,75)ST	✗	100		6.9	77
5749	(5X0,14)ST	✗	100	500	4.5	37
6717	(5X0,25)ST	✓	100	500	5.5	54.5
5750	(6X0,25)ST	✗	100	500	5.9	60
11165	(6X0,34)ST	✓	100		6.2	61
7006	(6X0,5)ST	✗	100	300	7.3	89
5752	(8X0,25)ST	✗	100		6.9	86
13479	(8X0,34)ST	✓	100	500	7.3	80
11980	(10X0,14)ST	✗	100	500	6.1	65
7439	(10X0,25)ST	✗	100		7.4	92
7047	(10X0,50)ST	✓	100	500	9.2	130
5753	(12X0,25)ST	✗	100		7.6	102
5754	(14X0,14)ST	✓	100	500	6.6	79
5755	(14X0,25)ST	✓	100	500	8	114
11981	(16X0,14)ST	✓	100		6.9	89
5756	(16X0,25)ST	✗	100		8.5	127
5757	(18X0,50)ST	✓		500	11.1	215
6526	(20X0,25)ST	✓	100	500	9.3	155
5758	(25X0,25)ST	✓		500	10.4	170
5759	(27X0,14)ST	✗	100		8.5	145
5760	(37X0,25)ST	✓		500	11.9	230

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.
Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.